

METRO STAINLESS SPECIFICATIONS

SHOWER BASE / TRAY

Stainless-steel. Thickness 1.5mm. Polished, Light Rotational Brush Finish
Fibreglass-reinforced underside. Fully supported, no flexing
Single-plane slope to integral channel-drain
Tray slope to rear, left or right hand side of tray
Glazing Channelling : Bright-Chrome Finish / Factory-installed
STANDARD SIZES: 160-plus. **CUSTOM SIZES** & Waste-outlet positions

ON-FLOOR TRAY

Threshold Height 65mm minimum. Threshold Width 50mm.
Installation onto timber or concrete floor.

LEVEL-ENTRY TRAY

Installation into a timber or concrete floor recess
with 18mm step-down from bathroom floor level

WHEELCHAIR-ACCESS TRAY

True, flush-entry (no step-down)
Installation onto rebated timber or concrete floor

CHANNEL-DRAIN EASY-CLEAN WASTE-TRAP

Easy-clean outlet dia. 40mm

CHANNEL-DRAIN COVER / GRATE OPTIONS

- (A) Stainless-steel -- Solid top
- (B) Stainless-steel -- Slotted top
- (D) Stainless-steel -- Tileable top
- (C) Stainless-steel -- Wedge-Wire (additional cost)

FRAMELESS-GLASS ENCLOSURE

Thickness: 10mm tempered / toughened safety glass
Standard Height: 2000mm (Optional Heights available)
NZS4223.3:2016 / AS/NZS 2208:1996 Compliant
Hinged door, Sliding door or 'Walk-In' panel-only options
Glazing Channel -- Standard: Bright-Polished finish
Optional finishes available

Hinges -- Standard: Chromed brass
Optional finishes available

Handles -- Standard: 'Round D' Polished stainless-steel
Optional designs available

LIQUID-APPLIED WALL WATERPROOFING MEMBRANES

Supplied by tiler or waterproofing sub-contractor.
See Recommended Waterproofing and Membranes list.

TRAY INSTALLATION

Tray to be installed with polymer-modified tile adhesive.
See Recommended Adhesives list.

FRAMELESS GLASS INSTALLATION

Impresa recommends the glass enclosure is installed by
an experienced frameless-glass installer.

WARRANTY

Shower Tray: 25-years
Frameless-Glass Enclosure: 10-years
Hardware: 5-years
See Warranty Statement

