



# METRO SPECIFICATIONS

## **SHOWER BASE / TRAY**

Aluminium / Marine-grade. Thickness 3mm. Epoxy-coated  
Single-plane slope to integral channel-drain at tray rear, left or right side  
Fibreglass-reinforced underside and support pads

### **Glazing Channelling**

Options: Matte Natural, Bright Polished, Brushed Stainless, Brushed Brass, Brushed Nickel, Black, Gunmetal  
Factory-installed to tray internal area

**STANDARD SIZES:** 160-plus. **Custom Sizes & Waste-outlet** positions

## **ON-FLOOR TRAY**

Threshold height 650mm minimum. Threshold width 35mm  
Installation onto timber or concrete floor

## **LEVEL-ENTRY TRAY**

Designed with 18mm step-down  
Installation onto rebated timber or concrete floor

## **WHEELCHAIR-ACCESS TRAY**

True, flush-entry (no step-down)  
Installation onto rebated timber or concrete floor

## **WASTE AND EASY-CLEAN TRAP OPTIONS**

PP Easy-Clean Trap: 40mm Inlet / 40mm Outlet  
Optional: Chromed Brass Waste: 40mm Dia. Inlet / Outlet (requires P or S Trap)  
ABS Easy-Clean Trap: 90mm Inlet / 50mm Outlet

## **CHANNEL-DRAIN COVER / GRATE OPTIONS**

- (A) Stainless-steel -- Solid top
- (B) Stainless-steel -- Slotted top
- (C) Stainless-steel -- Tileable Top
- (D) Stainless-steel -- Wedge-Wire (additional cost)

## **FRAMELESS-GLASS ENCLOSURE**

Thickness: 10mm tempered / toughened safety glass  
Standard Height: 2000mm (Optional Heights available)  
NZS4223.3:2016 / AS/NZS 2208:1996 Compliant  
Hinged door, Sliding door or 'Walk-In' panel-only options

**Glazing Channel** -- Standard: Matte-Aluminium finish  
Optional finishes available

**Hinges** -- Standard: Chromed brass  
Optional finishes available

**Handles** -- Standard: 'Round D' Polished stainless-steel  
Optional designs available

**Aluminium Brace Bar** and Clamp Brackets

## **LIQUID-APPLIED WALL WATERPROOFING MEMBRANES**

Supplied by tiler or waterproofing sub-contractor.  
See Recommended Waterproofing and Membranes list.

## **TRAY INSTALLATION**

Tray to be installed with polymer-modified tile adhesive.  
See Recommended Adhesives list.

## **FRAMELESS GLASS INSTALLATION**

Impresa recommends the enclosure is installed by an experienced frameless-glass installer.

## **TILE APPLICATION**

Direct-stick ceramic or porcelain tile to tray with Mapei Kerapoxy Adhesive or Sika Sikadur 32 Normal

## **WARRANTY**

Shower Tray: 25-years  
Frameless-Glass Enclosure: 10-years  
Hardware: 5-years

