

NEXUS stainless

NEXUS STAINLESS SPECIFICATIONS

SHOWER TRAY

Stainless-steel. Thickness 1.5mm. Polished, Light Rotational Brush Finish
Centre drain outlet
High-density foam supported underside

Standard Sizes / Shapes

Corner 900 x 900 1000 x 1000 1200 x 900 1200 x 1000
Alcove 900 x 900 1000 x 1000 1200 x 900 1200 x 1000
Angle 900 x 900 1000 x 1000

TRAY DESIGN

ON-FLOOR

Installation onto timber or concrete floor

LEVEL-ENTRY / WHEELCHAIR-ACCESS

Installation into rebated timber or concrete floor

EASY-CLEAN TRAP

Position: Centred
Trap Inlet: 90mm diameter
Trap Outlet: 40mm diameter
Flow Rate: 26 litres / min.

FRAMELESS-GLASS ENCLOSURE

Thickness: 10mm toughened glass
Standard Height : 2000mm
NZS 4223:2016 / AS/NZS 2208:1996 Compliance
Glazing Channel: Bright Chrome finish
Glazing Brace Bar and Overpanel Clamp Brackets
Hinges: Chrome-on-brass. Self-centring
Handle: Standard -- Stainless-steel Round 'D'

LIQUID-APPLIED WALL MEMBRANES

Supplied by tiler or waterproofing contractor

INSTALLATION

Tray to be installed with polymer-modified tile adhesive

FRAMELESS GLASS INSTALLATION

Frameless-glass enclosure to be installed by experienced frameless-glass installer

WARRANTY

Shower Tray: 15-years
Frameless-Glass Enclosure: 10-years
Hardware: 5-years
See Warranty Statement on website.