

NEXUS

NEXUS SPECIFICATIONS

SHOWER TRAY

Aluminium / Marine-grade. Thickness 3mm. Epoxy-coated

Centre drain outlet

High-density foam supported underside

Standard Sizes / Shapes

Corner 900 x 900 1000 x 1000 1200 x 900 1200 x 1000

Alcove 900 x 900 1000 x 1000 1200 x 900 1200 x 1000

Angle 900 x 900 1000 x 1000

TRAY DESIGN

ON-FLOOR

Installation onto timber or concrete floor

LEVEL-ENTRY / WHEELCHAIR-ACCESS

Installation into rebated timber or concrete floor

EASY-CLEAN TRAP

Position: Centre of tray

Trap Inlet: 90mm diameter

Trap Outlet: 40mm or 50mm Diameter

Flow Rate: 26 litres / min.

STAINLESS-STEEL GRATE

Square 140 x 140mm -- for ease of tile application

Linear Brush Finish

FRAMELESS-GLASS ENCLOSURE

Thickness: 10mm toughened glass

Standard Height : 2000mm

NZ Standard Compliant to NZS 4223:2016

Glazing Channel: Bright Chrome finish.

To be cut to size on-site

Glazing Brace Bar and Clamp Brackets

Hinges: Chrome-on-brass. Self-centring

Handle: Standard -- Stainless-steel Round 'D'

Optional Handles available

LIQUID-APPLIED WALL MEMBRANES

Supplied by tiler or waterproofing contractor

TRAY INSTALLATION

Tray to be installed with polymer-modified tile adhesive

FRAMELESS GLASS INSTALLATION

Frameless-glass enclosure to be installed by experienced frameless-glass installer

TILE APPLICATION

Direct-stick ceramic or porcelain tile to tray with Mapei

Kerapoxy Adhesive or Sika Sikadur 32 Normal

WARRANTY

Shower Tray: 15-years

Frameless-Glass Enclosure: 10-years

Hardware: 5-years

See Warranty Statement on website.