

### SHOWER TRAY

Stainless-steel. Thickness 1.5mm. Polished, Light Rotational Brush Finish  
Fibreglass-reinforced tray underside. Fully supported.

**Glazing Channelling** : Bright-Polished Finish / Factory-installed

**STANDARD SIZES**: 160-plus

**CUSTOM SIZES** and waste-outlet position optional

### ON-FLOOR TRAY

Installation onto timber or concrete floor  
Threshold Height 50mm. Threshold Width 50mm

### LEVEL-ENTRY TRAY (18mm step-down)

Installation onto rebated timber or concrete floor

### WHEELCHAIR-ACCESS TRAY (Flush-entry tray / no step-down)

Installation onto rebated timber or concrete floor

### EASY-CLEAN WASTE-TRAP

Standard Position: Centre or corner. Custom position optional

'Dome-Chrome' top

Trap outlet: 40mm diameter

Flow Rate: 26 litres / min. approx.

Optional Hi-flow Waste outlet: P or S-trap required

### FRAMELESS-GLASS ENCLOSURE

Thickness: 10mm tempered / toughened safety glass

Standard Height: 2000mm (Optional Heights available)

NZS4223.3:2016 / AS/NZS 2208:1996 Compliant

Hinged door, Sliding door or 'Walk-In' panel-only options

**Glazing Channel** -- Standard: Bright-Polished finish  
Optional finishes available

**Hinges** -- Standard: Chromed brass  
Optional finishes available

**Handles** -- Standard: 'Round D' Polished stainless-steel  
Optional designs available

**Glazing Brace Bar** and Clamp Brackets

### LIQUID-APPLIED WALL WATERPROOFING MEMBRANES

Supplied by tiler or waterproofing sub-contractor.

See Recommended Waterproofing and Membranes list.

### TRAY INSTALLATION

Tray to be installed with polymer-modified tile adhesive.

See Recommended Adhesives list.

### FRAMELESS GLASS INSTALLATION

Impresa recommends the enclosure is installed by an experienced frameless-glass installer.

### WARRANTY

Shower Tray: 25-years

Frameless-Glass Enclosure: 10-years

Hardware: 5-years

See Warranty Statement

