



STILE SHOWER SPECIFICATIONS

SHOWER BASE / TRAY

Marine-grade Aluminium. Thickness 3mm. Epoxy-coated
Fibreglass-reinforced underside. Fully supported, no flexing
Single-plane slope to waste-outlet or customised slope to optional
waste position

STANDARD SIZES: Over 100

CUSTOM SIZES / WASTE-OUTLETS positions optional

GLAZING CHANNEL

Standard: Matte Aluminium finish. Optional: Bright Chrome finish
Black powder-coated optional. Factory-installed to tray internal area

ON-FLOOR TRAY

Threshold height 50mm minimum. Threshold width 50mm.
Installation onto timber or concrete floor.

LEVEL-ENTRY TRAY

Designed with 18mm step-down
Installation onto rebated timber or concrete floor

WHEELCHAIR-ACCESS TRAY

True, flush-entry (no step-down)
Installation onto rebated timber or concrete floor

EASY-CLEAN WASTE-TRAP

Standard Position: Tray rear / front corner or Centre
Inlet Dia. 90mm. Outlet Dia. 40mm or 50mm

STAINLESS-STEEL GRATE OR TILE-INSERT

Square 140 x 140mm -- for ease of tile application

Linear Brush Finish

FRAMELESS-GLASS ENCLOSURE

Thickness: 10mm tempered / toughened safety glass
Standard Height: 2000mm (Optional Heights available)
NZS4223.3:2016 / AS/NZS 2208:1996 Compliant
Hinged door, Sliding door or 'Walk-In' panel-only options
Glazing Channel -- Matte Aluminium-finish standard supply
Optional finishes available

Hinges -- Standard: Chromed brass
Optional finishes available

Handles -- Standard: 'Round D' Polished stainless-steel
Optional designs available

Glazing Brace Bar and Clamp Brackets

LIQUID-APPLIED WALL WATERPROOFING MEMBRANES

Supplied by tiler / waterproofing sub-contractor.
See Waterproofing and Membranes list.

TRAY INSTALLATION

Tray to be installed with polymer-modified tile adhesive. See Recommended
Adhesives list.

FRAMELESS GLASS INSTALLATION

Impresa recommends the enclosure is installed by an experienced frameless-glass
installer.

TILE APPLICATION

Direct-stick ceramic or porcelain tile to tray with Mapei Kerapoxy Adhesive or Sika
Sikadur 32 Normal

WARRANTY

Shower Tray: 25-years
Frameless-Glass Enclosure: 10-years
Hardware: 5-years. See Warranty Statement

