

# URBIS stainless URBIS STAINLESS SPECIFICATIONS

## **SHOWER TRAY**

Stainless-steel. Thickness 1.5mm. Polished, Light Rotational Brush Finish  
Centre drain outlet  
Standard Sizes: 8  
High-density foam supported underside  
Tiling Membrane optional  
15-Year Leakproof Guarantee

## **ON-FLOOR TRAY**

Installation onto timber or concrete floor

## **LEVEL-ENTRY TRAY /**

### **WHEELCHAIR-ACCESS TRAY** (Flush-entry tray)

Installation onto rebated timber or concrete floor

## **CHANNEL-DRAIN WITH EASY-CLEAN TRAP**

Integral channel-drain  
Trap Inlet: 40mm diameter  
Trap Outlet: 40mm diameter

## **CHANNEL-DRAIN COVER**

Stainless-steel -- Solid Top  
Brush Finish

## **FRAMELESS-GLASS ENCLOSURE**

Thickness: 10mm toughened glass  
Standard Height : 2000mm  
NZS 4223:2016 / AS/NZS 2208:1996 Compliant  
Glazing Channel: Bright Chrome finish  
Glazing Brace Bar and Clamp Brackets  
Hinges: Chrome-on-brass. Self-centring  
Handle: Standard -- Stainless-steel Round 'D'

## **LIQUID-APPLIED WALL MEMBRANES**

Supplied by tiler or waterproofing contractor.  
See Recommended Waterproofing and Membranes list

## **TRAY INSTALLATION**

Tray to be installed with polymer-modified tile adhesive

## **FRAMELESS GLASS INSTALLATION**

Impresa recommends the glass enclosure be installed by experienced a frameless-glass installer

## **WARRANTY**

Shower Tray: 15-years  
Frameless-Glass Enclosure: 10-years  
Hardware: 5-years