

# URBIS

## URBIS SPECIFICATIONS

### SHOWER TRAY

Aluminium / Marine-grade. Thickness 3mm. Epoxy-coated  
Single-plane slope to centred waste-outlet hole at tray LH or RH side  
High-density foam supported underside

### Standard Sizes / Shapes

Corner 900 x 900 1000 x 1000 1200 x 900 1200 x 1000  
Alcove 900 x 900 1000 x 1000 1200 x 900 1200 x 1000

### TRAY DESIGN

#### ON-FLOOR

Installation onto timber or concrete floor

#### LEVEL-ENTRY

Installation into rebated timber or concrete floor

### CHANNEL DRAIN COVER / GRATE

Stainless-steel -- solid top (Linear brushed Finish)

### EASY-CLEAN TRAP

Position: Centre of tray  
Trap Inlet: 40mm diameter  
Trap Outlet: 40mm diameter  
Flow Rate: 26 litres / min.

### FRAMELESS-GLASS ENCLOSURE

Thickness: 10mm toughened glass  
Standard Height : 2000mm  
NZS 4223:2016 / AS/NZS 2208:1996 Compliant  
Glazing Channel: Bright Polished finish  
Glazing Brace Bar and Clamp Brackets  
Hinges: Chrome-on-brass. Self-centring  
Handle: Standard -- Stainless-steel Round 'D'

### LIQUID-APPLIED WALL MEMBRANES

Supplied by tiler or waterproofing contractor

### TRAY INSTALLATION

Tray to be installed with polymer-modified tile adhesive

### TILE APPLICATION

Direct-stick ceramic or porcelain tile to tray with Mapei  
Kerapoxy Adhesive or Sika Sikadur 32 Normal

### FRAMELESS GLASS INSTALLATION

Frameless-glass enclosure to be installed by experienced  
frameless-glass installer

### WARRANTY

Shower Tray: 15-years  
Frameless-Glass Enclosure: 10-years  
Hardware: 5-years  
See Warranty Statement on website.